

US007693608B2

US 7,693,608 B2

Apr. 6, 2010

(12) United States Patent

Nasle

(54) SYSTEMS AND METHODS FOR ALARM FILTERING AND MANAGEMENT WITHIN A REAL-TIME DATA ACQUISITION AND MONITORING ENVIRONMENT

(75) Inventor: Adib Nasle, Poway, CA (US)

(73) Assignee: EDSA Micro Corporation, San Diego,

CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 480 days.

(21) Appl. No.: 11/780,764

(22) Filed: Jul. 20, 2007

(65) Prior Publication Data

US 2008/0120080 A1 May 22, 2008

Related U.S. Application Data

- (63) Continuation-in-part of application No. 11/734,709, filed on Apr. 12, 2007, which is a continuation-in-part of application No. 11/717,378, filed on Mar. 12, 2007.
- (60) Provisional application No. 60/807,889, filed on Jul. 20, 2006, provisional application No. 60/792,175, filed on Apr. 12, 2006.
- (51) **Int. Cl. G06F 19/00** (2006.01)

(56) References Cited

U.S. PATENT DOCUMENTS

6,408,953	B1 *	6/2002	Goldman et al	175/39
2003/0200075	A1*	10/2003	Meng et al	703/22
2004/0249775	$\mathbf{A}1$	12/2004	Chen	
2005/0033481	A1	2/2005	Budhraja et al.	

(10) **Patent No.:**

(45) **Date of Patent:**

"Real-Time Knowledge Based Systems", Laffey et al, AI Magazine vol. 9 No. 1, 1988, AAAI.*

OTHER PUBLICATIONS

"Process monitoring and diagnosis: a model-based approach", - Dvorak et al, IEEE Expert 6(3):67-74, Jun. 1991.*

"Alarm processing in Electrical Power Systems Through a Neuro-Fuzzy Approach", Stacchini de Souze et al, IEEE Transactions on Power Delivery, vol. 19, No. 2, Apr. 2004.*

"Development of a real-time power system dynamic performance monitoring system", Lee et al, IEEE Transactions on Industry Applications. 1997.*

International Search Report for PCT/US07/73979 mailed Jun. 30, 2008.

* cited by examiner

Primary Examiner—Michael D Masinick (74) Attorney, Agent, or Firm—Procopio Cory Hargreaves & Savitch LLP; Noel C. Gillespie

(57) ABSTRACT

A system for filtering and interpreting real-time sensory data from an electrical system is disclosed. The system includes a data acquisition component, a power analytics server and a client terminal. The data acquisition component acquires real-time data output from the electrical system. The power analytics sewer is comprised of a virtual system modeling engine, an analytics engine, and a decision engine.

The virtual system modeling engine generates predicted data output for the electrical system. The analytics engine monitors real-lime data output and predicted data output of the electrical system. The decision engine compares the real-time data output against the predicted data output to filter out and interpret indicia of electrical system health and performance.

The client terminal is communicatively connected to the power analytics server and configured to display the filtered and interpreted indicia.

42 Claims, 24 Drawing Sheets

